

FIB20box96ip68closure Muffola IP68_6 imbocchi in/out_max. 96 fibre.

96 Core Fiber Optic Closure(6 in or out)

Description

optical splice closures are used to distribute, splice, and store the outdoor optical cables which enter and exit from the ends of the closure. There are two connection ways: direct connection and splitting connection. They are applicable to situations such as overhead, man-well of pipeline, embedded situation etc. Comparing with terminal box, the closure requires much stricter requirement of seal.

Features

- The closure casing is made of quality engineering PP plastics, and of good performance of anti-erosion against acid and alkali salt, anti-aging, as well as smooth appearance and reliable mechanical structure.
- The mechanical structure is reliable and has the performance of resisting wild environment and intensive climate changes and serious working environment. The protection grade reaches IP68.
- The splice trays inside the closure are turn-able like booklets, and have adequate curvature radius and space for winding optical fiber to make sure the curvature radius for optical winding 40mm. Each optical cable and fiber can be operated individually.
- The closure is of small volume, big capacity and convenient maintenance. The elastic rubber seal rings inside the closure are of good sealing and sweat-proof performance.



Configuration

Material	Size	Max Capacity	Diameter of Cable	Weight	Cable Entrance or Exit
Strengh then ABS	A*B*C(mm) 320*210*85	Splice 96 Fibers (4 trays,12/24 core for tray)	A : \varnothing 8 mm B : \varnothing 16 mm C : \varnothing 20 mm	2.8 kg	6 in or out

Applications

- Used for direct transmission of outdoor cable in aerial, duct and direct buried application.
- Used for branching connection and protect the joint.

Standard Accessories

- Metal spanner : 1pcs
- Metal hanger : 2pcs
- Sealing rubber strip : 1pcs
- Insulating tape : 1pcs
- Plastic plug : 9pcs
- Rubber waterproof strip : 2pcs
- Cable tie: 3mm*110mm 8pcs
- Screw: 9pcs
- Expension bolt: M6 4pcs
- Tag paper: 3pcs
- Heat-shrink sleeve: 1.2mm*60mm 48pcs

